

Safety Data Sheet

According to Annex II to REACH - Regulation (EU) 2020/878 and to Annex II to UK REACH

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Code: **MAM 515**
Product name **CRN WET SIZE 1723**

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use **COMBINED BLEACHING AGENT FOR BOTH CONTINIOUS AND DISCONTINIOUS PROCESSES**

1.3. Details of the supplier of the safety data sheet

Name **CRN BOYA KIMYA SAN. TIC. LTD. STI.**
Full address **ULUDAĞ ORGANİZE SANAYİ BÖLGESİ KALE MAH.KILIÇLAR CAD. NO:10 KESTEL**
District and Country **16450 BURSA TR**
Tel. **+90 224 372 50 23**
Fax **+90 224 372 50 29**

1.4. Emergency telephone number

For urgent inquiries refer to **+90 224 372 50 23**

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2020/878.

Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

| | | |
|--|------|---|
| Oxidising liquid, category 1 | H271 | May cause fire or explosion; strong oxidiser. |
| Acute toxicity, category 4 | H302 | Harmful if swallowed. |
| Acute toxicity, category 4 | H332 | Harmful if inhaled. |
| Skin corrosion, category 1A | H314 | Causes severe skin burns and eye damage. |
| Serious eye damage, category 1 | H318 | Causes serious eye damage. |
| Specific target organ toxicity - single exposure, category 3 | H335 | May cause respiratory irritation. |

2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:



Signal words: **Danger**

Hazard statements:

| | |
|------------------|---|
| H271 | May cause fire or explosion; strong oxidiser. |
| H302+H332 | Harmful if swallowed or if inhaled. |
| H314 | Causes severe skin burns and eye damage. |
| H335 | May cause respiratory irritation. |

Precautionary statements:

SECTION 2. Hazards identification ... / >

| | |
|-----------------------|--|
| P210 | Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. |
| P260 | Do not breathe dust / fume / gas / mist / vapours / spray. |
| P220 | Keep away from clothing and other combustible materials. |
| P305+P351+P338 | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. |
| P303+P361+P353 | IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]. |
| P280 | Wear protective gloves/ protective clothing / eye protection / face protection. |

Contains: HYDROGEN PEROXIDE SOLUTION
AMMONIUM BIS(2-ETHYLHEXYL) PHOSPHATE

2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage \geq than 0,1%.

The product does not contain substances with endocrine disrupting properties in concentration \geq 0.1%.

SECTION 3. Composition/information on ingredients**3.2. Mixtures**

Contains:

| Identification | x = Conc. % | Classification (EC) 1272/2008 (CLP) |
|----------------|-------------|-------------------------------------|
|----------------|-------------|-------------------------------------|

HYDROGEN PEROXIDE SOLUTION

| | | | |
|-------|--------------|-------------------|--|
| INDEX | 008-003-00-9 | 90 \leq x < 100 | Ox. Liq. 1 H271, Acute Tox. 4 H302, Acute Tox. 4 H332, Skin Corr. 1A H314, Eye Dam. 1 H318, STOT SE 3 H335, Classification note according to Annex VI to the CLP Regulation: B |
| EC | 231-765-0 | | Ox. Liq. 1 H271: \geq 70%, Ox. Liq. 2 H272: \geq 50%, Skin Corr. 1A H314: \geq 70%, Skin Corr. 1B H314: \geq 50%, Skin Irrit. 2 H315: \geq 35%, Eye Dam. 1 H318: \geq 8%, Eye Irrit. 2 H319: \geq 5%, STOT SE 3 H335: \geq 35% |
| CAS | 7722-84-1 | | LD50 Oral: 1193 mg/kg, STA Inhalation mists/powders: 1,5 mg/l, STA Inhalation vapours: 11 mg/l |

AMMONIUM BIS(2-ETHYLHEXYL) PHOSPHATE

| | | | |
|-------|-----------|----------------|-----------------|
| INDEX | | 5 \leq x < 8 | Eye Dam. 1 H318 |
| EC | 225-615-3 | | |
| CAS | 4971-47-5 | | |

The full wording of hazard (H) phrases is given in section 16 of the sheet.

SECTION 4. First aid measures**4.1. Description of first aid measures**

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 30-60 minutes, opening the eyelids fully. Get medical advice/attention.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention.

INGESTION: Have the subject drink as much water as possible. Get medical advice/attention. Do not induce vomiting unless explicitly authorised by a doctor.

INHALATION: Get medical advice/attention immediately. Remove victim to fresh air, away from the accident scene. If the subject stops breathing, administer artificial respiration. Take suitable precautions for rescue workers.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

4.3. Indication of any immediate medical attention and special treatment needed

Information not available

SECTION 5. Firefighting measures

5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Do not breathe combustion products.

5.3. Advice for firefighters

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage

7.1. Precautions for safe handling

Ensure that there is an adequate earthing system for the equipment and personnel. Avoid contact with eyes and skin. Do not breathe powders, vapours or mists. Do not eat, drink or smoke during use. Wash hands after use. Avoid leakage of the product into the environment.

7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store in a ventilated and dry place, far away from sources of ignition. Keep containers well sealed. Keep the product in clearly labelled containers. Avoid overheating. Avoid violent blows. Keep containers away from any incompatible materials, see section 10 for details.

7.3. Specific end use(s)

Information not available

CRN WET SIZE 1723

SECTION 8. Exposure controls/personal protection

8.1. Control parameters

Regulatory References:

GBR United Kingdom EH40/2005 Workplace exposure limits (Fourth Edition 2020)
 TLV-ACGIH ACGIH 2022

HYDROGEN PEROXIDE SOLUTION

| Threshold Limit Value | | | | | |
|-----------------------|---------|--------|------------|------------------------|-----|
| Type | Country | TWA/8h | STEL/15min | Remarks / Observations | |
| | | mg/m3 | ppm | mg/m3 | ppm |
| WEL | GBR | 1,4 | 1 | 2,8 | 2 |
| TLV-ACGIH | | 1,4 | 1 | | |

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

HAND PROTECTION

Protect hands with category III work gloves.

The following should be considered when choosing work glove material (see standard EN 374): compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION

Wear category III professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

EYE PROTECTION

Wear a hood visor or protective visor combined with airtight goggles (see standard EN 166).

In the presence of risks of exposure to splashes or squirts during work, adequate mouth, nose and eye protection should be used to prevent accidental absorption.

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, use a mask with a type A filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required. Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

| Properties | Value | Information |
|--------------------------------|----------------|-------------|
| Appearance | liquid | |
| Colour | colourless | |
| Odour | characteristic | |
| Melting point / freezing point | not available | |
| Initial boiling point | not available | |
| Flammability | not available | |
| Lower explosive limit | not available | |
| Upper explosive limit | not available | |
| Flash point | not available | |

SECTION 9. Physical and chemical properties ... / >

| | |
|--|------------------------|
| Auto-ignition temperature | not available |
| Decomposition temperature | not available |
| pH | 5,0-8,0 |
| Kinematic viscosity | not available |
| Solubility | not available |
| Partition coefficient: n-octanol/water | not available |
| Vapour pressure | not available |
| Density and/or relative density | 1,17 g/cm ³ |
| Relative vapour density | not available |
| Particle characteristics | not applicable |

Temperature: 20 °C

9.2. Other information**9.2.1. Information with regard to physical hazard classes**

Information not available

9.2.2. Other safety characteristics

Information not available

SECTION 10. Stability and reactivity**10.1. Reactivity****HYDROGEN PEROXIDE SOLUTION**

Decomposes if exposed to: light,heat.Decomposes on contact with: alkaline metals.Possibility of explosion.

10.2. Chemical stability

Information not available

10.3. Possibility of hazardous reactions

The product may react violently with water.

10.4. Conditions to avoid

Avoid overheating. Prevent moisture or water from penetrating inside the containers.

HYDROGEN PEROXIDE SOLUTION

Avoid exposure to: light,heat.Avoid contact with: alkaline substances.

10.5. Incompatible materials**HYDROGEN PEROXIDE SOLUTION**

Incompatible with: flammable substances,acetone,ethanol,glycerol,organic sulphides,hydrated bases,oxidising substances,iron,copper,bronze,chromium,zinc,lead,silver,manganese,acetic acid.

10.6. Hazardous decomposition products

Information not available

SECTION 11. Toxicological information

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

Information not available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

SECTION 11. Toxicological information ... />

Information not available

Interactive effects

Information not available

ACUTE TOXICITY

| | |
|--|---|
| ATE (Inhalation - mists / powders) of the mixture: | 1,50 mg/l |
| ATE (Inhalation - vapours) of the mixture: | 11,00 mg/l |
| ATE (Inhalation - gas) of the mixture: | Acute Tox. 4 |
| ATE (Oral) of the mixture: | 417,55 mg/kg |
| ATE (Dermal) of the mixture: | Not classified (no significant component) |

HYDROGEN PEROXIDE SOLUTION

LD50 (Oral): 1193 mg/kg Rat
at the concentration of 35%

AMMONIUM BIS(2-ETHYLHEXYL) PHOSPHATE

LD50 (Oral): > 3000 mg/kg

SKIN CORROSION / IRRITATION

Corrosive for the skin

SERIOUS EYE DAMAGE / IRRITATION

Causes serious eye damage

RESPIRATORY OR SKIN SENSITISATION

Does not meet the classification criteria for this hazard class

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

STOT - SINGLE EXPOSURE

May cause respiratory irritation

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class

11.2. Information on other hazards

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with human health effects under evaluation.

SECTION 12. Ecological information

Use this product according to good working practices. Avoid littering. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation.

12.1. Toxicity

**SECTION 12. Ecological information ... / >**

AMMONIUM BIS(2-ETHYLHEXYL) PHOSPHATE
EC50 - for Crustacea > 250 mg/l/48h

12.2. Persistence and degradability

HYDROGEN PEROXIDE SOLUTION
Solubility in water 100000 mg/l
Rapidly degradable

12.3. Bioaccumulative potential

HYDROGEN PEROXIDE SOLUTION
Partition coefficient: n-octanol/water -1,57

12.4. Mobility in soil

Information not available

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage \geq than 0,1%.

12.6. Endocrine disrupting properties

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with environmental effects under evaluation.

12.7. Other adverse effects

Information not available

SECTION 13. Disposal considerations**13.1. Waste treatment methods**

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Waste transportation may be subject to ADR restrictions.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14. Transport information**14.1. UN number or ID number**

ADR / RID, IMDG, IATA: 2014

14.2. UN proper shipping name

ADR / RID: HYDROGEN PEROXIDE, AQUEOUS SOLUTION
IMDG: HYDROGEN PEROXIDE, AQUEOUS SOLUTION
IATA: HYDROGEN PEROXIDE, AQUEOUS SOLUTION

SECTION 14. Transport information ... / >**14.3. Transport hazard class(es)**

ADR / RID: Class: 5.1 Label: 5.1 (8)



IMDG: Class: 5.1 Label: 5.1 (8)



IATA: Class: 5.1 Label: 5.1 (8)

**14.4. Packing group**

ADR / RID, IMDG, IATA: II

14.5. Environmental hazardsADR / RID: NO
IMDG: NO
IATA: NO**14.6. Special precautions for user**ADR / RID: HIN - Kemler: 58 Limited Quantities: 1 L Tunnel restriction code: (E)
Special provision: -
IMDG: EMS: F-H, S-Q Limited Quantities: 1 L
Cargo: Maximum quantity: 5 L Packaging instructions: 554
IATA: Passengers: Maximum quantity: 1 L Packaging instructions: 550
Special provision: -**14.7. Maritime transport in bulk according to IMO instruments**

Information not relevant

SECTION 15. Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**Seveso Category - Directive 2012/18/EU: P8Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

| | |
|----------------------------|----|
| <u>Product</u> | 3 |
| <u>Point</u> | 3 |
| <u>Contained substance</u> | |
| <u>Point</u> | 75 |

Regulation (EU) 2019/1148 - on the marketing and use of explosives precursors

Restricted explosives precursor

The acquisition, introduction, possession or use of that restricted explosives precursor by members of the general public is subject to a restriction as set out in Article 5(1) and (3). Restricted explosives precursors shall not be made available to, or introduced, possessed or used by members of the general public.

The acquisition, introduction, possession or use of that regulated explosives precursor by members of the general public is subject to reporting obligations as set out in Article 9.

All suspicious transactions and significant disappearances and thefts must be reported to the relevant national contact point.

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage \geq than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to Regulation (EU) 649/2012:

None

Substances subject to the Rotterdam Convention:

SECTION 15. Regulatory information ... / >

None

Substances subject to the Stockholm Convention:

None

Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

15.2. Chemical safety assessment

A chemical safety assessment has not been performed for the preparation/for the substances indicated in section 3.

SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

| | |
|----------------------|--|
| Ox. Liq. 1 | Oxidising liquid, category 1 |
| Acute Tox. 4 | Acute toxicity, category 4 |
| Skin Corr. 1A | Skin corrosion, category 1A |
| Eye Dam. 1 | Serious eye damage, category 1 |
| STOT SE 3 | Specific target organ toxicity - single exposure, category 3 |
| H271 | May cause fire or explosion; strong oxidiser. |
| H302 | Harmful if swallowed. |
| H302+H332 | Harmful if swallowed or if inhaled. |
| H332 | Harmful if inhaled. |
| H314 | Causes severe skin burns and eye damage. |
| H318 | Causes serious eye damage. |
| H335 | May cause respiratory irritation. |

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- ATE: Acute Toxicity Estimate
- CAS: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE: Identifier in ESIS (European archive of existing substances)
- CLP: Regulation (EC) 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: Regulation (EC) 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA: Time-weighted average exposure limit
- TWA STEL: Short-term exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
3. Regulation (EU) 2020/878 (II Annex of REACH Regulation)
4. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament

SECTION 16. Other information ... / >

6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
12. Regulation (EU) 2016/1179 (IX Atp. CLP)
13. Regulation (EU) 2017/776 (X Atp. CLP)
14. Regulation (EU) 2018/669 (XI Atp. CLP)
15. Regulation (EU) 2019/521 (XII Atp. CLP)
16. Delegated Regulation (UE) 2018/1480 (XIII Atp. CLP)
17. Regulation (EU) 2019/1148
18. Delegated Regulation (UE) 2020/217 (XIV Atp. CLP)
19. Delegated Regulation (UE) 2020/1182 (XV Atp. CLP)
20. Delegated Regulation (UE) 2021/643 (XVI Atp. CLP)
21. Delegated Regulation (UE) 2021/849 (XVII Atp. CLP)
22. Delegated Regulation (UE) 2022/692 (XVIII Atp. CLP)

- The Merck Index. - 10th Edition
- Handling Chemical Safety
- INRS - Fiche Toxicologique (toxicological sheet)
- Patty - Industrial Hygiene and Toxicology
- N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA website
- Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

CALCULATION METHODS FOR CLASSIFICATION

Chemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9.

Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section 11.

Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.